



Ultra-Thin Motorised TFT Monitor Lift





Product Parameters

- Available Sizes: 15.6", 17.3", 18.5", 21.5"
- Material: Aluminum alloy brushed panel, matt silver LCD frame.
- Used the RJ45 cable to connect to remote control
- Silver or Black
- High Definition Screen(15.6" and 17.3")
- Standard Definition Screen(18.5" and 21.5")
- Connect with USB, HDMI , VGA , Data, Input, Power
- HDMI ,VGA, USB type A for ON/OFF switch, USB type B for data, RJ45 connctor for RS485
- Tilt Angle : 0°-60°



NEW

- Monitor Retracts Vertically from desktop on press of a button
- First monitor tilt angle is 25 degree and then upto 60 degree adjustable
- Titring angle to make perfect viewing angle for users
- Virtually Silent working with excellent working life.

Panel Size: 430*80*6mm
 First cut out size 431*81*3mm
 Second Cut out size: 414*70mm
 The LCD box size: 414*70*551mm
 Weight:9 kg

- Control Way: Touch key-press/ Remote control/RS485 central control
- Panel: brushed aluminum panel edging processing, high-grade utility for more conference table installation. Used chain transmission up and down.
- This LCD monitor is provided with an Automatic power ON / OFF system. When the monitor is going up, the power is will be switched ON automatically. In order to save energy and preserve the work life of the monitor, in the opposite state the monitor will be completely switched OFF
- Control methods: Remote control RS485, central control, manual control
- LCD MONITOR LIFT using the control panel button, weakness contacts remote control, 485 code of centralized control combination, to adapt to various types of integrated system. Only 5 control button to complete the rising key, stop, the control key down key, 2* the monitor set key
- Remote Control Instructions
- * Long press OPEN and CLOSE button on the lift 5 seconds, the lift will ring one time.
- * In 10 seconds Press the remote control UP/STOP/DOWM Any one key, the lift will ring two times. the you can used the remote control

- SLIM CABINET:
 Depth of the monitor is adjusted to the minimum for an aesthetic and modern solution.

- SPECIFICATIONS FOR THE MONITOR
 LCD monitor size: 380*260*10mm
 LCD TYPE 15.6 IPS Monitor
 BRIGHTNESS: 265 CD/M2
 Colors: 16.7 million
 VIEWING ANGLE: 85/85/85/85(Typ.)(CR≥10)
 VIEWING AREA 381.9(W) x 214.8(H) mm

* 1,2 is "+" and 3, 4 is "-"

* First, have to use Serial Port to RJ11 Cable

